Initial Calibrations - Case 1640-1688 & 2x44-2x88 Combines

Monitor Serial No:

Flow Sensor Serial No:

Box Cal: Voltage Cal:

Header Sensor: Standard

Scale Factor: 1.0 Sensor Cal:

T1: 10 T2: 5 T3: 8

Sprocket Teeth: 9 Elevator Pulses/Rev: 1

Note: Be sure to set the above values before harvesting!

	1640/1660/1644/1666/2x44/2x66			1680/1688/2x88		
Crop	Soybeans/ Edible Beans	All Corn Types	All Other Grains	Soybeans/ Edible Beans	All Corn Types	All Other Grains
C1	100	100	100	100	100	100
C2	180	360	180	240	480	240
C3	360	720	360	480	960	480
C4	540	1080	540	720	1440	720
C5	720	1440	720	960	1920	960
C6	900	1800	900	1200	2400	1200
C7	1080	2160	1080	1440	2880	1440
C8	1260	2520	1260	1680	3360	1680
C9	1440	2880	1440	1920	3840	1920
C10	1620	3240	1620	2160	4320	2160
C11	1800	3600	1800	2400	4800	2400
S1	75	50	75	75	50	75
M1	400	650	705	400	650	705
% OFFSET	+4.7	+3.5	+2.0	+4.7	+3.5	+2.0

Ag Leader Technology

Rev A 9-11-00