

<b>Initial Calibrations - Lexion 570R, 575R (2006+ models)</b>					
<b>580R, 585R, 590R (All models)</b>					
					TF-4.9-085
<b>IMPORTANT: SPECIAL FIRMWARE REQUIRED</b>					
On power up, verify monitor screen displays "Grain Harvest/Site - SE"					
Monitor Serial No:				Header Sensor:	Standard
Flow Sensor Serial No:				Box Cal:	
Sensor Cal:				Voltage Cal:	
Scale Factor:	0.8			T1:	10
Elevator Sprocket Teeth:	11			T2:	5
Elevator Speed Pulses/Rev:	4			T3:	8
<b>Note: Be sure to set the above values before harvesting!</b>					
		Soybeans/ Edible Beans	All Corn Types	All Other Grains	
C1	100	100	100		
C2	350	700	350		
C3	700	1400	700		
C4	1050	2100	1050		
C5	1400	2800	1400		
C6	1750	3500	1750		
C7	2100	4200	2100		
C8	2450	4900	2450		
C9	2800	5600	2800		
C10	3150	6300	3150		
C11	3500	7000	3500		
S1	0	0	0		
M1	400	650	705		
	% OFFSET	+4.7	+3.5	+2.0	<b>Ag Leader Technology</b>
Rev A					7/18/2006