Initial Calibrations - Deere 6600/7700/6620/7720 Combines

Monitor Serial No:

Flow Sensor Serial No:

Header Sensor: Standard

Box Cal: Voltage Cal:

Sensor Cal:

6600/7700/6620 Scale Factor: 2.0

7720 Scale Factor: 1.8

T1: 10 T2: 5 T3: 8

Sprocket Teeth: 8 Elevator Pulses/Rev: 1

Note: Be sure to set the above values before harvesting!

	6600/7700/6620 (6" elevator/4" impact plate)			7720 (6" elevator/3" impact plate)		
Crop	Soybeans Edible Beans	All Corn Types	All Other Grains	Soybeans Edible Beans	All Corn Types	All Other Grains
C1	100	100	100	100	100	100
C2	150	300	150	200	400	200
C3	300	600	300	400	800	400
C4	450	900	450	600	1280	600
C5	600	1200	600	800	1600	800
C6	750	1500	750	1000	2000	1000
C7	900	1800	900	1200	2400	1200
C8	1050	2100	1050	1400	2800	1400
C9	1200	2400	1200	1600	3200	1600
C10	1350	2700	1350	1800	3600	1800
C11	1500	3000	1500	2000	4000	2000
S1	75	50	75	75	50	75
M1	400	650	705	400	650	705
% OFFSET	+4.7	+3.5	+2.0	+4.7	+3.5	+2.0

Ag Leader Technology

Rev N/C 2-25-98