

## PF3000 Initial Calibrations - Gleaner R40/50/42/52 Combines

PF3000 Initial Calibrations - Gleaner R40/50/42/52 Combines						
Monitor Serial No:						
Flow Sensor Serial No:						
Header Sensor:		Reversed			Box Cal:	
					Sensor Cal:	
Scale Factor:		1.5			Voltage Cal:	
Elevator Sprocket Teeth:		8			T1:	10
Elevator Speed Pulses/Rev:		6 or 7 *			T2:	5
* R42-R52 1995+ models set to 6. (Low shaft speed sensor on lower auger)					T3:	8
R42-R52 1994 and previous models set to 7. (Low shaft speed sensor on upper auger)						
R40-R50 set to 6.						
<b>Note: Be sure to set the above values before harvesting!</b>						
Crop	Soybeans/ Edible Beans	All Corn Types	All Other Grains			
C1	100	100	100			
C2	220	440	220			
C3	440	880	440			
C4	660	1320	660			
C5	880	1760	880			
C6	1100	2200	1100			
C7	1320	2640	1320			
C8	1540	3080	1540			
C9	1760	3520	1760			
C10	1980	3960	1980			
C11	2200	4400	2200			
S1	75	50	75			
M1	400	650	705			
% OFFSET	+4.7	+3.5	+2.0	<b>Ag Leader Technology</b>		
Rev N/C					2/25/1998	