

| Initial Calibrations - Gleaner R62/R72 Combines                            |                           |                   |                     |                             |              |    |
|--|---------------------------|-------------------|---------------------|-----------------------------|--------------|----|
| Monitor Serial No:   |                           |                   |                     |                             |              |    |
| Flow Sensor Serial No:   |                           |                   |                     |                             |              |    |
| Header Sensor:   | Reversed                  |                   |                     |                             | Box Cal:     |    |
|  |                           |                   |                     |                             | Sensor Cal:  |    |
| Scale Factor:  | 1.0                       |                   |                     |                             | Voltage Cal: |    |
| Elevator Sprocket Teeth:   | 8                         |                   |                     |                             | T1:          | 10 |
| Elevator Speed Pulses/Rev:   | 6 or 7 *                  |                   |                     |                             | T2:          | 5  |
| * 1995+ models set to 6. (Low shaft speed sensor on lower auger)           |                           |                   |                     |                             | T3:          | 8  |
| 1994 and previous models set to 7. (Low shaft speed sensor on upper auger) |                           |                   |                     |                             |              |    |
| <b>Note: Be sure to set the above values before harvesting!</b>            |                           |                   |                     |                             |              |    |
| Crop   | Soybeans/<br>Edible Beans | All<br>Corn Types | All Other<br>Grains |                             |              |    |
| C1   | 100                       | 100               | 100                 |                             |              |    |
| C2   | 330                       | 660               | 330                 |                             |              |    |
| C3   | 660                       | 1320              | 660                 |                             |              |    |
| C4   | 990                       | 1980              | 990                 |                             |              |    |
| C5   | 1320                      | 2640              | 1320                |                             |              |    |
| C6   | 1650                      | 3300              | 1650                |                             |              |    |
| C7   | 1980                      | 3960              | 1980                |                             |              |    |
| C8   | 2310                      | 4620              | 2310                |                             |              |    |
| C9   | 2640                      | 5280              | 2640                |                             |              |    |
| C10  | 2970                      | 5940              | 2970                |                             |              |    |
| C11  | 3300                      | 6600              | 3300                |                             |              |    |
| S1   | 75                        | 50                | 75                  |                             |              |    |
| M1   | 400                       | 650               | 705                 |                             |              |    |
| % OFFSET   | +4.7                      | +3.5              | +2.0                | <b>Ag Leader Technology</b> |              |    |
| Rev N/C  |                           |                   |                     |                             | 2/25/1998    |    |